

HTM1D

B&W
Bowers & Wilkins



The HTM1D is the largest of four centre speakers in the 800 Series. The full configuration of FST™ midrange in a Marlan® sphere / tube ‘head’ with diamond dome tweeter on top is used, so that the system perfectly voice matches either the 800D, 801D or 802D in a substantial and powerful multi-channel installation.

The HTM1D uses three 8” diameter Rohacell® cone drivers with twin rear-firing Flowports™. All drivers are, of course, magnetically shielded to avoid picture distortion with CRT-based screens.

The HTM1D is specifically intended to be mounted on the floor, its low profile allowing a large projection screen to come within 2 ft. of the floor. Supplied with the system are four heavy-duty height-adjustable feet. This design allows up to 1.6” of vertical adjustment so that the speaker may be tilted back to face more towards the listeners. They have a case hardened spike at one end for carpeted floors, and a non-marking rubber pad on the other for more vulnerable surfaces.

Description: 3-way vented-box system

Frequency Range: -6dB at 32Hz and 33kHz

Frequency Response: 38Hz – 28kHz ±3dB on reference axis

Sensitivity: 90dB spl (2.83V, 1m)

Nominal Impedance: 8Ω (minimum 3.7Ω)

Dimensions: H 585mm W 974mm D 580mm
H 23” W 38.3” D 22.8”
(not including feet)

Weight: 93 kg / 205 lbs.

Finishes: Cherrywood, Rosenut, Black Ash

B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England

T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk