



SA250 Mk2 Technical Specifications

Description

250W rack-mount amplifier with built-in subwoofer equalisation

Amplifier inputs

- 2x RCA Phono socket, line in
- 2x RCA Phono socket, link out
- 1x XLR socket, line in
- 1x XLR socket, link out
- 3.5mm jack - 12V trigger on/standby (overrides manual standby setting)
- 3.5mm jack - 12V trigger equalisation movie/music

Amplifier outputs

- 1x Neutrik® Speakon® 4-pole speaker socket
- 2x pairs of Binding Posts

Amplifier power output

250W

Input impedance

33k Ω

Signal / noise

>80dB

Rated power consumption

95W – 1/8 full power
30W – Idling

Dimensions

Height: 100mm (3.9 in)
[88.5mm (3.5 in) plus feet]
Width: 430mm (16.9 in)
Depth: 322mm (12.7 in)
Front panel Height: 2U 88.1mm/3.5 in

Net weight

5.4kg (11.9 lb)

Finish

Black

Bowers & Wilkins

www.bowers-wilkins.com

Kevlar is a registered trademark of DuPont.
Speakon is a registered trademark of Neutrik AG
Copyright © B&W Group Ltd. E&OE
B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments