Bowers & Wilkins

Custom Installation CCM8.5 D




See nothing, hear everything

CCM8.5 D is a two-way in-ceiling loudspeaker which offers high-quality acoustics in an incredibly discreet package.

It features a decoupled Diamond dome tweeter and a single 7inch bass/midrange Continuum driver with anti-resonance plug. All the drive units are located in a rotatable mini-baffle which allows the user to 'toe in' the drive units of the loudspeaker for the best performance.

For optimum discretion when installed, the Continuum cone is given a dark finish.



Technical Specifications

Description 2-way in-ceiling loudspeaker

Technical features Aluminium Tweeter 'wing'

Rotatable aluminium mini-baffle allows 'toe-in' Diamond Dome, Nautilus™ tube-loaded tweeter Anti-resonance plug

Flowport™

Drive units 1x Ø25mm (1in) Diamond Dome,

Nautilus™ tube-loaded tweeter

1x Ø180mm (7in) Continuum cone bass/midrange driver with anti-resonance plug

Frequency range (-6dB) 35Hz - 35kHz

Recommended

Amplifier Power 120W

Sensitivity 88dB

Nominal Impedance 8Ω

Frame (width/height) 351mm (13.8in)

Cut-out (width/height) 331mm (13in)

Protrusion 8mm (0.3in)

Net weight 5kg

Back Box BB CCM8.5

Bowers & Wilkins

www.bowers-wilkins.com